

# EcoPouch®<sup>®</sup>, Powered by Nano-VpCI®<sup>®</sup> Patented US #8,800,224



## PRODUCT DESCRIPTION

EcoPouch® contains VpCI®-609 powder for corrosion protection of ferrous metals and aluminum. The pouches are constructed from breathable Tyvek®, which allows the VpCI® molecules to be emitted through the membrane, and form a molecular layer on metal surfaces providing corrosion protection.

EcoPouch® is easy to use: there are no chemical concentrations to calculate and no need for special equipment for application; just determine the number of pouches required per unit space. EcoPouch® provides a clean method for corrosion protection.

EcoPouch® is available as individually cut pouches, and each pouch protects up to 35ft<sup>3</sup>. Custom sizes and constructions are also available.

## FEATURES

- Creates inhibiting layer on metal surface
- Provides continuous long term protection for various applications
- Does not contain nitrites, phosphates, or heavy metals



## ADVANTAGES

- Vapor-phase inhibiting action protects inaccessible and recessed surfaces
- Protected products can be shipped directly to customers; no need to remove protective VpCI® film after arrival, just remove pouch
- If the VpCI® layer is disturbed by moisture or the opening of an enclosed space, the layer is replenished by continuous vapor redeposition
- Little or no surface preparation is required
- Prevents future corrosion of precoated and painted surfaces
- Clean and easy to use

## TYPICAL USES

- Tubular structures, pipes, and vessels
- Internal surfaces of compressors, turbines, engines, tanks, boilers, heat exchangers
- Steam condensate lines, closed circuit heating, and cooling systems
- Corrosion protection of equipment after hydrostatic testing
- Parts, components, and completed assemblies during shipping and storage
- Voids, cavities, and tanks
- Double bottom storage tank floors

## TOXICOLOGICAL TESTING RESULTS OF VpCI®-609 (Performed by Nortech A.S. (Norway))\*

- Biodegradability: 100% biodegradable in marine environment, rapidly degradable substance (OECD\*\* 306, BOD 28 Marine test)
- Toxicity: Very low (Algae test EC-50=240 mg/L)
- Bioaccumulation potential: none (OECD Guideline 117)

\*Testing performed in accordance with Oslo-Paris commission protocol

\*\*Organization for Economic Co-Operation and Development



## TYPICAL PROPERTIES

Form	Tyvek® breathable pouch
Appearance	White with green printing
Dimensions	Each pouch is 6" W x 10" L x 0.5" H (15.3cm x 25.4cm x 1.3cm)

## METALS PROTECTED

- Carbon steel
- Mild steel
- Stainless steel
- Other ferrous metals
- Aluminum

## METHOD OF APPLICATION

Determine the number of pouches required based upon the volume of space needing protection. Each pouch protects up to 1 m<sup>3</sup> (35 ft<sup>3</sup>). Evenly distribute pouches throughout the space and close or seal.

Custom sizes and constructions also available. Please contact a Cortec® Representative for more information.

## PRECAUTIONS

Do not use on copper, copper-based alloys, and other soft yellow metals. Compatibility with non-metals should be evaluated.

**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**  
**CONSULT SAFETY DATA SHEET FOR MORE INFORMATION**

## PACKAGING AND STORAGE

EcoPouches are available as 50 units per carton. Do not store in conditions above 150°F (65°C). Close cartons between uses. The shelf life of unopened cartons of EcoPouches is up to 24 months.

### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.  
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Environmentally Safe VpCI®/MCI® Technologies

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 09/08/17. Supersedes: 08/08/17. ©Cortec Corporation 2002-2017 of Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2017, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by:



ניצוץ - עשיה לתעשיה

077-5240590

[www.glimmer.co.il](http://www.glimmer.co.il)

[office@glimmer.co.il](mailto:office@glimmer.co.il)